

533 533
Rec'd PCT/PTO 02 MAY 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

10/533533

(10) International Publication Number
WO 2004/040249 A1

(51) International Patent Classification⁷: G01J 5/34,
5/20, 1/42

Joseph [GB/GB]; 11 Nettleton Grove, Blackley, Manchester M9 4BQ (GB). CONNERADE, Jean, Patrick [GB/GB]; 76 Granville Road, London SW18 5SG (GB). GARCIA-SEGUNDO, Crescencio [MX/GB]; 53 Cromwell Road, London SW7 2EH (GB).

(21) International Application Number:
PCT/GB2003/004630

(22) International Filing Date: 28 October 2003 (28.10.2003) (74) Agent: MATHISEN, MACARA & CO.; 6-8 Sakeleys Road, Ickenham, Uxbridge, Middlesex UB10 8BZ (GB).

(25) Filing Language: English

(81) Designated States (national): JP, US.

(26) Publication Language: English

(84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(30) Priority Data:
0225396.1 31 October 2002 (31.10.2002) GB

Published:


- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventors; and
(75) Inventors/Applicants (for US only): SMITH, Alan,



(54) Title: A DEVICE FOR REFLECTING AND DETECTING ELECTROMAGNETIC RADIATION



WO 2004/040249 A1

(57) Abstract: A device for simultaneously detecting and reflecting electromagnetic radiation consisting of a thin layer of insulating pyro-electric and/or piezo-electric material sandwiched between two conducting electrodes. The upper-most electrode is effective to separate the radiation into a reflected part and an unreflected part, which is absorbed, and the insulating layer has an electrical property dependent on the intensity of electromagnetic radiation absorbed by the upper-most electrode. An electrical voltage and/or current measured between the two electrodes is responsive to the electrical property of the insulating layer and is indicative of the intensity of the absorbed electromagnetic radiation.